



PM1508

HAND-HELD INSULATION TESTER

- Dual LCD display with backlit
- Insulation test from $0.1\text{M}\Omega$ to $20\text{G}\Omega$ with DC voltages 50V /100V /250V /500V /1000V
- Auto discharge, Measures
- **DAR /PI** and comparison measurement
- Auto zero for low resistance measurement
- Data hold, auto power-off
- Integrated protection holster, safety as per IEC1010-1 Cat.III 600V

Technical specifications

DCV: 0~600.0V, $\pm 1.5\%$

ACV: 1.0~600.0V (50/60Hz), $\pm 1.5\%$

Low OHM /Continuity: 0.00~200 Ω , $\pm 2.0\%$

FREQ: 1~1kHz, $\pm 0.1\%$

Insulation:

50V /100V/250V/500V/1000V:

0.00M Ω ~ 10G Ω , $\pm 1.5\%$ ~10%

1000V: 10G~ 20G Ω , $\pm 10\%$; 20G~ 100G Ω , $\pm 20\%$

DAR: 60s:15s, 60s:30s

PI: 10 min:1 min

Compare: 20 values from 100k Ω to 500M Ω

Audible continuity (<30 Ω)

Battery: 1.5Vx4, AA size, alkaline

Dimensions: 189x93.8x55mm, 450g approx

PEAKMETER®

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn