



PM16A

WORKSHOP DMM WITH TORCH LAMP

- 2,000 counts LCD display with backlit
- Non-Contact AC voltage detection in 3 levels
- Live wire detection with single test lead
- Audible continuity test in 3 levels
- **Extra bright torch lamp** built on back
- **Input socket light indication**
- Data hold, Max value measurement
- Auto ranging, auto power-off
- 10A/600V fused, full ranges protection
- Safety as per IEC 1010-1 Cat.III 600V

Technical specifications

DCV: 200m/2/20/200/600V, $\pm 0.5\%$

ACV: 2/20/200/600V, $\pm 1.0\%$

DCA: 200m/2m/20m/200m/10A, $\pm 1.0\%$

ACA: 200m/2m/20m/200m/10A, $\pm 1.2\%$

OHM: 200/2k/20k/200k/2M/20M Ω , $\pm 0.8\%$

BAT: 1.5V /9V

Continuity: $<40 \Omega$, $40 \Omega \sim 60 \Omega$, $>60 \Omega$

Diode test: 1mA/3.2V

Dimensions & weight: 150x75x50mm, 300g

Battery: 1.5Vx4, AAA size

Accessories: holster

PEAKMETER®

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn