



PM19D True RMS

WORKSHOP DMM WITH TORCH LAMP

- 6,000 counts LCD display with backlit
- Non-Contact AC voltage detection in 3 levels
- Live wire detection with single test lead
- Audible continuity test in 3 levels
- **Extra bright torch lamp** built on back
- True RMS AC measurement (40Hz~1kHz)
- Display frequency at ACV /ACA measurement
- Data hold, auto power-off
- 10A/1000V fused, full ranges protection
- Safety: Cat.III 1000V and Cat. IV 600V

Technical specifications

DCV: 600m/6/60/600/1000V, $\pm 0.5\%$

ACV: 6/60/600/750V, $\pm 0.8\%$

DCA: 60 μ /6m/60m/600m/10A, $\pm 0.8\%$

ACA: 60m/600m/10A, $\pm 1.0\%$

OHM: 600/6k/60k/600k/6M/60M Ω , $\pm 0.8\%$

CAP: 6n/60n/600n/6 μ /60 μ /600 μ /6m/100mF, $\pm 4.0\%$

FREQ: 60/600/6k/60k/600k/6M/10MHz, $\pm 1.0\%$

Duty cycle: 5%~95%, $\pm 2.0\%$

Continuity: <40 Ω , 40 Ω ~60 Ω , >60 Ω

Diode test: 1mA/3.2V

Dimensions & weight: 190x89x50mm, 380g approx.

Battery: 1.5Vx4, AA size

Accessories: holster

PEAKMETER®

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn