



PM2017B

600A AC AUTO-RANGING CLAMP METER

- 6000 counts LCD display with backlit
- Non-contact AC voltage detection (NCV)
- Single probe live wire detection
- **VFD** (Variable-frequency Drive) measurement
- **True RMS** AC measurement
- Max /Min and relative measurement
- Data hold
- Auto /manual ranging, auto power off
- Safety as per IEC1010-1 CAT.III 1000V

Technical specifications

DCV: 6/60/600/1000V, $\pm 0.5\%$

ACV: 6/60/600/1000V, $\pm 0.8\%$ (40~400Hz)

ACA: 6/60/600A, $\pm 2.5\%$

OHM: 600/6k/60k/600k/6M/60M Ω , $\pm 1.0\%$

CAP: 60n/600n/6 μ /60 μ /600 μ /6m/60mF, $\pm 4.0\%$

FREQ: 10/100/1k/10k/100k/1MHz, $\pm 1.0\%$

TEMP: -20 $^{\circ}$ C~1000 $^{\circ}$ C, -4 $^{\circ}$ F~1832 $^{\circ}$ F, $\pm 2.0\%$

Audible continuity: <50 Ω

Clamp size: $\Phi 35$ mm (max.)

Battery: 1.5Vx2, AAA size

Dimensions: 195x66x33mm

Weight: 189g approx.

PEAKMETER®

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn