

# PM8225C True RMS

## ELEGANT POCKET DMM WITH TORCH

- 6000 counts LCD display with bargraph
- Non-Contact voltage and live wire detection
- VFD (variable-frequency drive) measurement
- True RMS AC measurement (45Hz~1kHz)
- Max/Min and Relative measurement
- Built-in **torch lamp**
- Data hold, auto ranging, auto power-off
- With holster and back stand, safety as per IEC1010-1 Cat.III 600V

### Technical specifications

DCV: 60m/600m/6/60/600V,  $\pm 0.5\%$

ACV: 60m/600m/6/60/600V,  $\pm 0.8\%$

DCA: 600 $\mu$ /6m/60m/600m/6/10A,  $\pm 0.8\%$

ACA: 600 $\mu$ /6m/60m/600m/6/10A,  $\pm 1.0\%$

OHM: 600/6k/60k/600k/6M/60M  $\Omega$ ,  $\pm 1.2\%$

CAP: 10n/100n/1 $\mu$ /10 $\mu$ /100 $\mu$ /1m/10m/100mF,  $\pm 3.0\%$

FREQ: 10/100/1k/10k/100k/1M/10MHz,  $\pm 1.0\%$

Duty Cycle: 1%~99%,  $\pm 3.0\%$

Audible continuity ( $<30 \Omega$ ), diode test

NCV: buzzer /bargraph indication of voltage level

Battery: 1.5Vx2, AAA size

Dimensions: 166x78x48mm

Weight: 252g approx.



**PEAKMETER®**

by Sinometer

[www.peak-meter.cn](http://www.peak-meter.cn)

Email: [sales@peak-meter.cn](mailto:sales@peak-meter.cn)