

PM8225D True RMS

ELEGANT POCKET DMM WITH TORCH

- 6000 counts LCD display with bargraph
- Non-Contact voltage and live wire detection
- **VFD** (variable-frequency drive) measurement
- **True RMS** AC measurement (45Hz~1kHz)
- Max/Min and Relative measurement
- Built-in **torch lamp**
- Data hold, auto ranging, auto power-off
- With holster and back stand, safety as per IEC1010-1 Cat.III 600V

Technical specifications

DCV: 60m/600m/6/60/600V, $\pm 0.5\%$

ACV: 60m/600m/6/60/600V, $\pm 0.8\%$

DCA: 600 μ /6m/60m/600m/6/10A, $\pm 0.8\%$

ACA: 600 μ /6m/60m/600m/6/10A, $\pm 1.0\%$

OHM: 600/6k/60k/600k/6M/60M Ω , $\pm 1.2\%$

CAP: 10n/100n/1 μ /10 μ /100 μ /1m/10m/100mF, $\pm 3.0\%$

FREQ: 10/100/1k/10k/100k/1M/10MHz, $\pm 1.0\%$

Duty Cycle: 1%~99%, $\pm 3.0\%$

TEMP: -20 $^{\circ}$ C~1000 $^{\circ}$ C, -4 $^{\circ}$ F~1832 $^{\circ}$ F, $\pm 2.0\%$

Audible continuity (<30 Ω), diode test

NCV: buzzer /bargraph indication of voltage level

Battery: 1.5Vx2, AAA size

Dimensions: 166x78x48mm, 252g approx.



PEAKMETER®

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn